

Intensive fast setting Sheefted Offset Inks

Performance Properties

- A robust resin system able to run with Eco friendly **fountain** solutions
- Fast setting and drying ideal for all press formats including perfectors
- High strengths for maximum mileage
- Optimized rheology's for efficient transfer
- Superb gloss and dot sharpness to enhance print quality
- 48 hour duct freshness
- Good rub resistance
- Excellent transfer to prevent picking of loosely bound fibres

Characteristics

- Excellent high speed printing stability
- Intensive color strength
- Excellent dot reproduction
- Complied with European color standard 12647-2

Storage

Care should be taken to store ink in tightly closed containers located in a cool (60-80°F/15-27°C) dark place. With suitable conditions, unopened ink is expected to have a shelf life of approximately twelve (12) months for colors and six (6) months for white, from date of manufacturer.

A. Warranty Liability Limited to Purchase and Installation Costs

Notwithstanding anything provided herein or any other written material to the contrary, Polymeric only warrants the purchase price and costs of installation. POLYMERIC SHALL HAVE NO LIABILITY OR OBLIGATION TO ANY USER, BUYER, PURCHASER, DISTRIBUTOR OR OTHER PERSON OR ENTITY FOR ANY SPECIAL, DIRECT, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, HOWEVER CAUSED, INCLUDING WITHOUT LIMITATION, PERSONAL INJURY, LOSS OF BUSINESS, LOSS OF PROFIT, OR OTHER DAMAGE, whether or not buyer shall have informed Polymeric of the possibility or likelihood of any such damages.

B. Limitation of Implied Warranty and Fitness for a Particular Purpose

POLYMERIC'S WARRANTY IS GIVEN IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO AN IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, AN IMPLIED WARRANTY OF MERCHANTABILITY, AND ANY OTHER IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, PERFORMANCE, CUSTOMER USAGE OR TRADE.

Applications

May be used on a wide variety of stocks and presses. Will accept water borne coatings and machine varnish.

UV varnishing is recommended between 2 and 48 hours after printing, but testing is recommended as results may vary between suppliers.

It is advisable to apply water-based primer before uv varnishing to pre-empt any issues

Wax-free colors and a lightfast yellow and magenta are available on request.

Precautions

Read the safety data sheet prior to processing. It contains instructions for precautions to be taken when handling inks. If ink comes in contact with skin wipe off with a clean, dry cloth (do not use solvent). Wash and rinse the affected areas with soap and water.