



## Technical Bulletin

### #18472 Anti-Graffiti Clear

UV Screen & Roll-coatings

Polymeric has developed a reliable Anti-Graffiti/Dry Erasable Clear for styrene and other commonly used Point of Purchase substrates. This ink has shown excellent adhesion to many popular general or multi-purpose POP UV inks.

- Anti-Graffiti Clear adheres well to styrene, acrylic, polyester, coated metal, coated cardboard stock and other related rigid materials
- Ideal for Bus Stop, Train Station, and Airport Terminal applications
- Works best against Aerosol or Enamel Spray Paint
- Exterior life – One year
- Spray Paint can be removed with acetone, alcohol and or high-pressure water
- Non-blocking, low tack finish for easy handling

#### APPLICATION:

<b>Mixing:</b>	The Anti-Graffiti Clear is supplied at print-ready viscosity and can be used directly from the container. Thinning is not recommended
<b>Deposit: Screen or Roll-coat</b>	0.5 to 1.0 mil
<b>Cure Parameters:</b>	1 - 200 watt per inch medium pressure mercury vapor lamp with an Mj output of at least 180
<b>Belt Speed:</b>	50 - 60 feet per minute (15 - 18 meters) depending on lamp efficiency and heat emission
<b>Coverage:</b>	3000 - 3500 square feet per gallon

**Note: DO NOT USE ON FLEXIBLE BANNER APPLICATIONS**

*As a quality control measure, please check Anti-Graffiti properties before proceeding with production runs. WARNING: This product will not perform if it has been under-cured, as there will be a penetration of paint, permanently staining the print.*

**More than a shade superior**

117 East 14<sup>th</sup> Avenue • N. Kansas City, MO 64116 • 800 746 5567 • fax: 816 221 4820