

MATERIAL SAFETY DATA SHEET

SECTION I

POLYMERIC IMAGING INC.
117 E. 14TH AVENUE
N. KANSAS CITY, MO 64116
DAYTIME PHONE:800-746-5567
24 HOUR PHONE:(CHEMTREC)800-424-9300
ISSUED: 11.21.08
REVISED:
REVISION NUMBER:

PRODUCT NAME: JETGREEN
PRODUCT CODE: 18478, 18479,
18480, 18481
COMMON NAME: UV CURABLE
DIGITAL INK
HMIS
HEALTH: 2
FLAMMABILITY: 1
REACTIVITY: 1

SECTION II COMPONENTS

COMPONENTS	CAS #	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
ACRYLATE ESTER BLEND	TS	NE	NE	
INITIATOR	TS	NE	NE	
COLORANT	TS	NE	NE	
RESIN	TS	NE	NE	

ALL COMPONENTS USED ARE EITHER LISTED OR EXCLUDED FROM LISTING ON THE TSCA INVENTORY.

CONTAINS NO HAPS CHEMICALS

*SARA TITLE III SECTION 313 INFORMATION:

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE ANNUAL REPORTING REQUIREMENTS OF SECTION 313 TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR 372.

NONE

DOT/IATA SHIPPING INFORMATION

DOT: NOT REGULATED

IATA: NOT REGULATED

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: °CELSIUS/°FAHRENHEIT	>150°C
VAPOR PRESSURE: MMHG	<1 MM HG @20°C
VAPOR DENSITY: AIR=1	HEAVIER THAN AIR
SPECIFIC GRAVITY: H2O=1	NA
MELTING POINT: °CELSIUS/°FAHRENHEIT	NA
EVAPORATION RATE: BUTYL ACETATE=1	NA
VOC'S	NEGLIGIBLE
SOLUBILITY IN WATER:	NEGLIGIBLE
APPEARANCE AND ODOR:	PIGMENTED, VARIES BY COLOR

SECTION IV**FIRE AND EXPLOSION HAZARD DATA**

FLASHPOINT: °CELSIUS/°FAHRENHEIT	>200°F
FLAMMABLE LIMITS:	
LEL	UNKNOWN
UEL	UNKNOWN
EXTINGUISHING MEDIA:	ALCOHOL FOAM CO2
	DRY CHEMICAL WATER FOG
CORROSIVE:	NO

SPECIAL FIREFIGHTING PROCEDURES:

FULL PROTECTIVE EQUIPMENT IS RECOMMENDED TO PROTECT FIRE FIGHTERS FROM ANY HAZARDOUS DECOMPOSITION PRODUCTS. WATER MAY BE UNSUITABLE FOR USE ON BURNING LIQUIDS. IF WATER MUST BE USED, FOG NOZZLES ARE HIGHLY PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO-IGNITION, EXPLOSION, OR RUPTURE WHEN EXPOSED TO EXTREME HEAT.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAMES. CLOSED CONTAINERS MAY RUPTURE OR EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CONSTITUTE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

SECTION V**REACTIVITY DATA**

STABILITY:	UNDER NORMAL CONDITIONS	CONDITIONS TO AVOID:	STRONG ACIDS, OXIDIZERS, ALKALI METAL HYDROXIDES, POLYMERIZATION INITIATORS, PEROXIDES, INERT GASES, AMINES, EXTREME TEMPERATURES, DIRECT SUNLIGHT, XRAY SOURCES, ELECTRON BEAM SOURCES, UV RADIATION SOURCES
HAZARDOUS DECOMPOSITION OR BYPRODUCTS			CARBON MONOXIDE, CARBON DIOXIDE, MIXED OXIDES OF NITROGEN, SULFUR AND METHACRYLATE MONOMERS
HAZARDOUS POLYMERIZATION			SEE ABOVE

SECTION VI**HEALTH HAZARD DATA**

ROUTES OF ENTRY:	INHALATION, EYE, SKIN, INGESTION
HEALTH HAZARDS: ACUTE/CHRONIC	MAY CAUSE SKIN SENSITIZATION, DERMATITIS. ACRYLATES HAVE BEEN REPORTED TO BE MUTAGENIC ONLY IN THE MOUSE LYMPHOMA ASSAY, BUT NEGATIVE IN THE AMES TEST.
CARCINOGENICITY:	NONE KNOWN
NTP: OSHA:	UNKNOWN

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

INGESTION: MAY CAUSE IRRITATION OF THE MOUTH, THROAT, ESOPHAGUS, AND STOMACH. THERE MAY BE DISCOMFORT OR PAIN IN THE MOUTH, THROAT, CHEST AND ABDOMEN, WITH NAUSEA, VOMITING, DIARRHEA, DIFFICULTY SWALLOWING, WEAKNESS, THIRST, DIZZINESS, AND DROWSINESS. ASPIRATION INTO THE LUNGS MAY OCCUR DURING INGESTION OR VOMITING, RESULTING IN LUNG INJURY.

INHALATION: EXPOSURE TO VAPORS IS UNLIKELY DUE TO LOW VAPOR PRESSURE OF INGREDIENTS, BUT INHALATION OF MIST, AEROSOLS, OR VAPORS MAY RESULT IN IRRITATION OF RESPIRATORY TRACT COUGHING, SHORTNESS OF BREATH AND DIZZINESS.

SKIN: CONTAINS MATERIAL THAT MAY CAUSE SEVERE SKIN IRRITATION (REDDENING AND SWELLING) AND/OR SENSITIZATION. PROLONGED CONTACT MAY CAUSE BLISTER FORMATION (BURNS). SINCE IRRITATION MAY NOT OCCUR IMMEDIATELY, CONTACT CAN GO UNNOTICED.

EYE: CONTAINS MATERIALS THAT MAY CAUSE MODERATE IRRITATION, INCLUDING BURNING SENSATION TEARING, REDNESS OR SWELLING.

MEDICAL CONDITIONS KNOWN TO BE AGGRAVATED BY OVEREXPOSURE: LUNG CONDITIONS, SENSITIZATION, OR ALLERGIES, SKIN AND EYE CONDITIONS.

MEDICAL CONDITONS AGGRAVATED BY EXPOSURE:

DERMATITUS, LUNG CONDITIONS(I.E. ASTHMA), SENSITIZATION, ALLERGIES, SKIN AND EYE CONDITIONS.

EMERGENCY AND FIRST AID PROCEDURES:

INGESTION: DRINK TWO GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY. BE PREPARED TO PROVIDE THE ATTENDING PHYSICIAN WITH A COPY OF THIS DOCUMENT.

INHALATION: REMOVE VICTIM TO A WELL VENTILATED AREA. GIVE OXYGEN OR ARTIFICIAL RESPIRATION AS REQUIRED. TREAT SYMPTOMATICALLY AND CONSULT PHYSICIAN.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH MILD SOAP AND WARM WATER. CONSULT A PHYSICIAN IF THERE IS ANY PERSISTING IRRITATION.

EYE CONTACT: FLUSH WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST FIFTEEN MINUTES. CONSULT PHYSICIAN.

SECTION VII**PRECAUTIONS FOR SAFE HANDLING & USAGE**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PLACE LEAKING CONTAINERS IN A WELL VENTILATED AREA. AVOID BREATHING VAPORS. ELIMINATE ALL SOURCES OF HEAT, AS WELL AS ALL CONDITIONS NOTED IN SECTION VII, ABOVE. NOTIFY PROPER AUTHORITIES IF PUBLIC WATERS OR SEWERS ARE CONTAMINATED.

WASTE DISPOSAL METHODS:

AS A HAZARDOUS WASTE, THIS MATERIAL MUST BE DISPOSED OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL ORDINANCES. INQUIRE OF YOUR LOCAL ENVIRONMENTAL AGENCIES FOR THE EXACT LEGAL REQUIREMENTS IN YOUR AREA.

REFER TO SECTIONS IV, V, VI, VII AND IX OF THIS DOCUMENT BEFORE ATTEMPTING ANY CLEANUP.

SECTION VIII CONTROL MEASURES

RESPIRATORY PROTECTION:

EXPOSURE TO VAPORS IS UNLIKELY DUE TO LOW VAPOR PRESSURE OF INGREDIENTS, BUT INHALATION OF MIST, AEROSOLS OR VAPORS MAY RESULT IN IRRITATION OF RESPIRATORY TRACT COUGHING, SHORTNESS OF BREATH AND DIZZINESS. IF VAPORS OR MIST EXCEEDS AIR MONITORING LEVELS, A NIOSH APPROVED RESPIRATOR MAY BE USED.

VENTILATION:

LOCAL EXHAUST RECOMMENDED WHEN APPROPRIATE TO CONTROL EXPOSURE TO MISTS OR AEROSOLS. GENERAL EXHAUST IS NORMALLY ADEQUATE TO MINIMIZE EXPOSURE TO VAPORS.

PROTECTIVE EQUIPMENT:

GLOVES

GOGGLES

SAFETY GLASSES

APRON

RESPIRATOR

WORK/HYGIENIC PRACTICES:

WASH HANDS BEFORE EATING, USING TOBACCO PRODUCTS, OR USING THE WASHROOM. TOBACCO AND FOOD SHOULD BE CONSUMED IN DESIGNATED AREAS ONLY.

PURCHASERS OBLIGATION

POLYMERIC URGES THE CUSTOMER RECEIVING THIS MATERIAL SAFETY DATA SHEET TO STUDY IT CAREFULLY TO BECOME AWARE OF HAZARDS, IF ANY OF THE PRODUCTS INVOLVED. IN THE INTEREST OF SAFETY, YOU SHOULD (1) NOTIFY YOUR EMPLOYEES, AGENTS AND CONTRACTORS OF THE INFORMATION ON THIS SHEET, (2) FURNISH A COPY TO EACH OF YOUR CUSTOMERS FOR THIS PRODUCT, AND (3) REQUEST YOUR CUSTOMERS TO INFORM THEIR EMPLOYEES, CUSTOMERS AND AGENTS AS WELL.

DISCLAIMER

POLYMERIC MAKES NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OR RELIABILITY OF INFORMATION CONTAINED HEREIN, EXCEPT THAT SUCH INFORMATION IS, TO THE BEST OF POLYMERIC'S KNOWLEDGE AND BELIEF, ACCURATE AS OF THE DATE INDICATED ON THIS DOCUMENT. FINAL DETERMINATION OF SUITABILITY OF MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.